

DIA. DASH NO.	A HEAD DIA. ±.005	B HEAD HEIGHT REF.	L REF.	C ±.010	D ±.005	E ±.004	F ±.003	G REF.	M ±.010	GRIP RANGE	SHEAR STRENGTH (LBS.)		TENSILE STRENGTH (LBS.)	INSTALLATION HOLE SIZE	DRILL SIZE
											△	△			
-4	.170	.065	2.80	.256	.188	.127	.135	.360	.312	.375-1.250	455	600	590	.1285-.132	#30
-5	.212	.085	2.50	.320	.258	.155	.168	.250	.344	.170-1.125	625	865	950	.160-.164	#20
-6	.256	.108	2.50	.385	.310	.175	.200	.360	.375	.375-1.250	875	1250	1650	.192-.196	#10

COLLAR		STEM	
MATERIAL	FINISH	MATERIAL	FINISH
△ 5056 ALUM. OR 2017 ALUM.	ANODIZE RED	7075 T6 ALUM.	CHEM. FILM ORANGE

△ OPTIONAL DRILL START IDENTIFIED BY "D" AT END OF THE PART NUMBER.


△ MAY BE 2017 ALUMINUM AT MANUFACTURERS OPTION.

△ COMPONENTS MAY BE LUBRICATED TO ENHANCE PERFORMANCE AT MFG'S DISCRETION.

△ VALUE GIVEN FOR SHEAR PLANE THROUGH "F" DIAMETER.

△ VALUE GIVEN FOR SHEAR PLANE THROUGH "E" DIAMETER.

EXAMPLE PART NUMBER:



U.S. PATENT: 6,772,500

**UNCONTROLLED COPY
WILL NOT BE KEPT UP TO DATE**

REV.	DATE	BY	E.O. NO.	PREPARED	CHECKED	APPROVED
G	05/14/04	J.Y.	5037	EDGAR MARIN	APPROVAL	ON FILE
H	04/23/07	L.D.	6071			
J	09/16/10	P.M.	7107			
K	11/07/11	P.M.	7549	<p style="text-align: center;">ALLFAST</p> <p style="text-align: center;">15200 DON JULIAN ROAD . CITY OF INDUSTRY CA. 91745 PHONE: (626) 968-9388</p>		
L	02/01/13	P.M.	8009			
M	06/13/14	P.M.	8553			