

**TABLE I**

PART NUMBER	Ø NOM		Ø A THEO		Ø A' MIN		C MAX		Ø D		F WRENCH FLATS		(H)		Ø J MAX		K MAX		R. R		S MAX	
	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm	INCH	mm
PLT6009-05-(-)	.1635	4,153	.290 .282	7,37 7,16	.253	6,43	.285	7,24	.1645 .1625	4,178 4,128	.086 .081	2,18 2,06	.051	1,30	.244	6,20	.257	6,53	.030 .010	0,76 0,25	.012	0,30
PLT6009-06-(-)	.1980	5,029	.357 .349	9,07 8,87	.313	7,95	.320	8,13	.1990 .1970	5,055 5,004	.104 .099	2,64 2,51	.065	1,65	.300	7,62	.288	7,32	.030 .015	0,76 0,38	.015	0,38
PLT6009-08-(-)	.2590	6,579	.480 .472	12,19 16,99	.436	11,07	.355	9,02	.2600 .2580	6,604 6,553	.135 .130	3,43 3,30	.091	2,31	.384	9,75	.320	8,13	.030 .015	0,76 0,38	.015	0,38
PLT6009-10-(-)	.3105	7,887	.568 .559	14,43 14,20	.510	12,95	.440	11,18	.3115 .3095	7,912 7,861	.152 .147	3,86 3,73	.107	2,72	.427	10,85	.396	10,06	.040 .020	1,02 0,51	.020	0,51
PLT6009-12-(-)	.3735	9,487	.698 .688	17,73 17,48	.632	16,05	.525	13,34	.3745 .3725	9,512 9,462	.185 .180	4,70 4,57	.134	3,40	.516	13,11	.473	12,01	.040 .020	1,02 0,51	.023	0,58

**TABLE I (CONTINUED)**

PART NUMBER	V (GAGE PROTRUSION)		Ø W (GAGE)		BREAK-OFF LIMITS		MINIMUM AVAILABLE GRIP LENGTH (TABLE II)	HOLE SIZE		PREVAILING TORQUE MIN		DOUBLE SHEAR STRENGTH MIN		TENSILE STRENGTH MIN	
	INCH	mm	INCH	mm	INCH	mm		INCH	mm	IN-LBS	Nm	LBS	N	LBS	N
PLT6009-05-(-)	.0302 .0258	0,767 0,655	.2195 .2193	5,575 5,570	+0.020 -0.068	+0.51 -1.73	-02	.168 .165	4,27 4,19	1.0	0,113	3150	14010	900	4000
PLT6009-06-(-)	.0385 .0338	0,978 0,859	.2671 .2669	6,784 6,779	+0.015 -0.073	+0.38 -1.85	-02	.202 .199	5,13 5,05	1.5	0,170	4600	20460	1400	6230
PLT6009-08-(-)	.0458 .0408	1,163 1,036	.3731 .3729	9,477 9,472	+0.010 -0.078	+0.25 -1.98	-03	.263 .260	6,68 6,60	2.5	0,282	7900	35140	2100	9340
PLT6009-10-(-)	.0582 .0524	1,478 1,331	.4320 .4318	10,973 10,968	+0.010 -0.083	+0.25 -2.11	-02	.315 .312	8,00 7,92	3.5	0,400	11350	50480	3600	16010
PLT6009-12-(-)	.0654 .0589	1,661 1,496	.5451 .5449	13,846 13,840	+0.010 -0.093	+0.25 -2.36	-03	.378 .375	9,60 9,52	4.0	0,452	16450	73170	5600	24910



APPLICABLE SPECIFICATIONS:  
 PROCUREMENT SPECIFICATION: 23M128 AND ESCBB 9  
 PART NUMBER ASSIGNMENT: PLT5001  
 INSTALLATION AND REMOVAL: PLT5002  
 SPECIAL LUBE AND FINISH: PLT5003

**MATERIAL:**  
 NUT AND SCREW: 6Al-4V TITANIUM ALLOY PER AMS4928 OR AMS4967.  
 SLEEVE: CRES.  
 DRIVE NUT: MILD STEEL.

**HEAT TREAT:**  
 NUT AND SCREW: HEAT TREAT TO 95 KSI ULTIMATE SHEAR STRENGTH.  
 SLEEVE: AS REQUIRED FOR PERFORMANCE.  
 DRIVE NUT: AS REQUIRED FOR PERFORMANCE.

**FINISH:**  
 NUT AND SCREW: NONE.  
 SLEEVE: PASSIVATE PER AMS2700.  
 DRIVE NUT: CORROSION RESISTANT COATING, COLOR GRAY.

**LUBRICATION:**  
 NO CODE ( ): SOLID DRY FILM LUBRICANT PER THE CHEMICAL REQUIREMENTS OF AS5272 TYPE I OR EVERLUBE 812 PER MIL-PRF-81329, PARAFFIN WAX AND/OR CETYL ALCOHOL PER AS87132 MAY BE APPLIED TO ANY OR ALL COMPONENTS AS REQUIRED FOR PERFORMANCE. (SEE PLT5003 FOR SPECIAL LUBRICANTS AND FINISHES).

**EXAMPLE PART NUMBER:**




TABLE II				
2ND DASH NO. △	GRIP RANGE			
	GRIP MIN		GRIP MAX	
	INCH	mm	INCH	mm
-02	.094	2.39	.156	3.96
-03	.157	3.99	.219	5.56
-04	.220	5.59	.281	7.14
-05	.282	7.16	.344	8.74
-06	.345	8.76	.406	10.31
-07	.407	10.34	.469	11.91
-08	.470	11.94	.531	13.49
-09	.532	13.51	.594	15.09
-10	.595	15.11	.656	16.66
-11	.657	16.69	.719	18.26
-12	.720	18.29	.781	19.84
-13	.782	19.86	.844	21.44
-14	.845	21.46	.906	23.01
-15	.907	23.04	.969	24.61
-16	.970	24.64	1.031	26.19
-17	1.032	26.21	1.094	27.79
-18	1.095	27.81	1.156	29.36
-19	1.157	29.39	1.219	30.96
-20	1.220	30.99	1.281	32.54
-21	1.282	32.56	1.344	34.14
-22	1.345	34.16	1.406	35.71
-23	1.407	35.74	1.469	37.31
-24	1.470	37.34	1.531	38.89
-25	1.532	38.91	1.594	40.49
-26	1.595	40.51	1.656	42.06
-27	1.657	42.09	1.719	43.66
-28	1.720	43.69	1.781	45.24
-29	1.782	45.26	1.844	46.84
-30	1.845	46.86	1.906	48.41
-31	1.907	48.44	1.969	50.01
-32	1.970	50.04	2.031	51.59

**GENERAL NOTES:**

1. LOCKING FEATURE CONSISTS OF THREE (3) INDENTATIONS LOCATED 120 ° APART ON THE PERIPHERY OF THE NUT COMPONENT.
2. HALF GRIP SIZES MAY BE ORDERED BY ADDING ".5" TO THE GRIP DASH NUMBER. EXAMPLE: PLT6009-06-4.5 INDICATES A NOMINAL GRIP LENGTH OF 4.5 SIXTEENTHS = .281" [7,14 mm] AND A GRIP RANGE OF .250" [6,35 mm] THRU .312" [7,92 mm].
3. ALTERNATE HEAD MARKING: "N" (OR "VS"), "1061".
4. HEAD MARKINGS ON NUT DEPRESSED .010 INCH [0,254 mm] MAXIMUM. POSITION OPTIONAL.
5. DRIVE NUT NOT SHOWN FOR CLARITY OF HEAD MARKINGS.

**MONOGRAM AEROSPACE FASTENERS**  
 a TriMas company  
 3423 SOUTH GARFIELD AVENUE  
 COMMERCE, CALIFORNIA 90040  
 (323) 722-4760 FAX (323) 727-1029

TITLE:  
 VISU-LOK® II, FASTENER, BLIND,  
 100° FLUSH SHEAR HEAD, NOMINAL DIAMETER  
 TITANIUM ALLOY

DRAWING NO:  
 PLT6009 ( ) - ( ) - ( )

DRAWN BY: A PEREZ  
 DRAWN DATE: 01/04/2014

APPROVED BY:  
 CHECKED DATE:

**PROPRIETARY AND CONFIDENTIAL:**  
 NOTICE: THIS DRAWING IS PART OF THE PROPRIETARY ARTICLE HEREIN DISCLOSED, OWNED BY MONOGRAM AEROSPACE FASTENERS. ANY PARTY BY ACCEPTING THIS DOCUMENT ASSUMES CUSTODY THEREOF AND AGREES:  
 A: THE INFORMATION SET FORTH HEREIN IS GIVEN IN CONFIDENCE AND THIS DOCUMENT WILL NOT BE COPIED OR REPRODUCED IN WHOLE OR IN PART, NOR ITS CONTENTS REVEALED IN ANY MANNER TO ANY PERSON EXCEPT TO MEET THE PURPOSE FOR WHICH IT WAS DELIVERED.  
 B: WITHOUT THE WRITTEN CONSENT OF MONOGRAM AEROSPACE FASTENERS, THIS DOCUMENT AND THE INFORMATION CONTAINED HEREIN UNDER NO CIRCUMSTANCES WILL BE USED IN THE MANUFACTURE OR REPRODUCTION OF THE ARTICLE DISCLOSED, AND THE DELIVERY OF THIS DOCUMENT SHALL NOT CONSTITUTE ANY RIGHT OR LICENSE TO DO SO.

**Alcoa**  
 CAGE CODE: 5M902

**MONOGRAM**  
 CAGE CODE: 98524

ECN NO: 14-0820  
 ECN DATE: 11/23/14

REV: C  
 SHEET 2 OF 2